



Product Information:

## **GOLDEN FILM RUNNING IN OIL FOR NEW OR REBUILT ENGINES**

### **Description**

Golden Film running-in oil is a speciality SAE 30 product that should be used for the running in of new or rebuilt petrol and diesel engines, where it promotes the quick and safe bedding in of mating surfaces. The use of Golden Film running-in oil during the running in period helps to remove the machining glaze from cylinder bores, assists the formation of essential oil retaining surfaces, and therefore prevents the possibility of bore polishing.

Careful running-in using this product can prevent any problems during this period and can greatly extend engine life. Golden Film running-in oil is blended from high quality mineral oils and a carefully balanced additive system.

### **Directions for Use**

Golden Film running-in oil should be used for 25 hours or 500 miles to permit controlled wear allowing surfaces to mate and bed-in.

### **Performance Levels**

MIL-L-2104B

### **Physical Characteristics**

SAE Classification	30
Appearance	Amber Liquid
Density @ 15°C	0.874
Viscosity @ 40°C (cSt)	90.4
Viscosity @ 100°C (cSt)	11.2
Viscosity Index	100
Closed Flash Point (°C)	230
Pour Point (°C)	-33
TBN (mgKOH/g)	10.5

Figures based on average production values.

Part No.s: ARU005, ARU025, ARU205

(TDS Golden Film Running In Oil – 291015 Issue 3)

