

Product Information:

# SUPERCUT 1000

## HIGH OIL CONTENT WATER SOLUBLE COOLANT



### Description

Supercut 1000 is a water soluble metalworking fluid of the traditional type. It is manufactured from high quality paraffinic base oils with added preservatives along with lubricity and anti-corrosion additives.



The product is readily miscible with most mains water to form a stable, rich, milky white emulsion of low odour and good corrosion protection. Supercut 1000 is non-staining to both ferrous and non-ferrous alloys and may be used in a wide variety of applications e.g. Turning (including light automatic work), milling, drilling, boring and shaping.



### Features

- Chlorine / Phenol / Nitrite Free
- Low Odour
- Economical
- Good Corrosion Protection

### Applications

General Machining, free machining metals, non-critical grinding, ferrous and non-ferrous alloys.

General Machining Concentration: 5% typical

Ferrous Grinding Concentration: 4% typical

**Higher concentrations of up to 10% may be employed for more arduous applications.**

### Physical Characteristics

Appearance (neat)	Amber liquid
Relative Density @ 15.6°C	0.901
Emulsion Appearance (5% in 200ppm water)	Milky White liquid
pH @ 25°C (5% aqueous)	9.10
IP 287 Rust Prevention Characteristics (200ppm water)	4% (25:1)
Foaming Tendency (5% in 200ppm water)	< 20 secs collapse time

Figures based on average production values

Part No.S: UNI005, UNI025, UNI205

(TDS Supercut 1000 – 210316 Issue 3)

